

HEAVY MACHINERY GENERAL SAFETY
GUIDELINES

Official Corporate Safety Standard & Operator Hazard Prevention Guide

DOC ID: KOR-SAF-2026-01
DATE: Jan 2026
STATUS: OFFICIAL

1. Personal Protective Equipment (PPE) Mandatory Requirements

All operators of KOREVA9 heavy agricultural machinery, walk-behind power weeders, and tractor implements must wear certified PPE before starting machinery:

- Steel-toe footwear with anti-slip rubber soles.
- Heavy-duty leather work gloves during implement coupling and blade handling.
- Safety goggles (ANSI Z87.1 approved) for protection against flying debris.
- Ear defenders or earplugs when operating machinery exceeding 85 dB noise level.

2. Field Operating Safety Perimeter & Slope Rules

IMPORTANT SAFETY ADVISORY: Maintain a strict 15-meter (50-foot) safety perimeter around active machinery. Never allow bystanders, children, or livestock near rotary blades or PTO drive shafts.

Operating Hazard	Mandatory Safety Procedure
Slope Operations	Do not operate walk-behind weeders or tractors on slopes exceeding 15 degrees to prevent tipping.
PTO Engagement	Disengage PTO drive before turning sharp corners or raising implements.
Clogged Blades	Shut off engine and disconnect spark plug cap BEFORE attempting to remove weeds or debris from rotavator blades.
Refueling Safety	Never refuel engine while hot or running. Allow 5 minutes cooling time before opening fuel tank cap.

3. Corporate Safety Support & Authorized Dealer Contact

For replacement safety decals, operator manuals, or technical assistance, contact KOREVA Global LLP technical support team at +91 7455 973 188 or email info@koreva.com.